



ELECTRICAL INFORMATION:

- 1. DCR [2-6]= 186 mohm Nom, [8-13] = 6.0 mohm Nom,
- 2. Inductance [2-6] = 1.2mH Nom, 1.08 Min, 1.32 Max @100KHz, 1.0 VRMS @ 25C
- 3. Leakage Inductance [2-6]= Short [8-13] = 4.0 uH Nom @100 KHz
- 4. Dielectric Strength 6 Sec Min: [2,6] to [8,13] :Core 3750 VAC II [8,13] :Core 500 Vdc
- 5. Weight 30 grams Max | RoHS Compliant | Pin Composition Tin/Silver Plating
- 6. Volt-usec Rating = 1020 @100C
- 7. Operating Ambient Temp Rating: -55C to +130C [Inclusive of Temp Rise]

No.	DESCRIPTION	REVISIONS	DATE	APPR
THIRD ANGLE PROJECTION				
CHAMPS TECHNOLOGIES				
DRAWN		SIGN	DATE	Champs No. 80R2-12AC-3124005-1M2
CHKD		HE	3/5/12	Customer ISSUE REV
APPR				Part #: A 00
TOLERANCES +/- 1.0 UNLESS OTHERWISE INDICATED			SIZE	SCALE 150%
.XXX ± .25				
.XX ± .51				
.X ± 1.0				
ANGLE ±				