



Electrical Information:

1. TURNS RATIO [2-6] : [9-13] = 0.462 +/-2% || [1-7] : [2-6] = 0.25 +/-2%
2. INDUCTANCE [2-6] = 480 uH Nom @100kHz/1.0V
3. LEAKAGE INDUCTANCE [2-6] : SHORT 9-13 = 400 nH Max @100kHz
4. DCR [2-6] = 28 mohms Nom, DCR [9-13] = 140 mohms Nom, DCR [1-7] = 300 mohm max
5. CAPACITANCE 2,6 to 9,13 = 90 pF Max @100kHz
6. DIELECTRIC ISOLATION: [2,6],[1,7] : [9,13] > 2250 Vdc
DIELECTRIC ISOLATION: [9,13] : CORE > 500 Vdc
7. RoHS Level 6/6 Compliant | Pins 96/4 Sn/Ag Plating

					CHAMPS TECHNOLOGIES	TOLERANCES UNLESS OTHERWISE INDICATED .xxx ± .xx ± .x ±	DRAWN	JL	11/18/14	TITLE: D26R6-1226-03		ISSUE	REV
							CHKD	PH			SIZE	SCALE 2:1	A
No.	DESCRIPTION	REVISIONS	DATE	APPR			APPR	DT					